





## rack.case PE.11U.480 | B&W rack case 480 mm housing

### Description

- Ruggedized roto-molded case body made from impact resistant PE material
- Shock mounts for maximum protection during transit
- 80 mm or 120 mm lid with edge wheels
- Standard 19" Rack width designed to meet ANSI/EIA-310-C
- Square hole rack rails to accommodate 6 mm standard cage nuts
- Heavy-duty polymer handles with soft rubber grip
- Stainless Steel Catches
- Mechanical Pressure Relief Valve (Standard)
- Watertight gasket between body and lid
- Lid hangers (standard)
- Various color options
- Available in **380 mm – 480 mm – 610 mm – 780 mm** rack depths
- Size ranges **3U to 14U**
- Multibrix® stacking and storage system (secure stacking and cross stacking of same or different size cases).
- Gridlines featured on the lid are specially designed for pallet strapping
- Light Weight compact design
- Standard payload range 20-75 kg
- Tested and Approved – MIL-STD 810 G, STANAG 4280, Def Stan 81-41
- IP 65 rated for dust and water ingress

The rack.cases are also available in other colors on request.

You can find a complete overview of all available sizes and configurations in our [product overview](#).

**Outer Dimensions Length (mm) :** 641

**Outer Dimensions Width (mm) :** 776

**Outer Dimensions Depth (mm) :** 570

**Weight (kg) :** 25,3

**Possible Equipment :** 4 handles, pressure valve, U height: 11U